

ECB 10022 SS
Floor Mounted Combination Unit of Drench Shower and Eyewash with Stainless Steel Bowls c/w Foot Pedal



Our combination unit of drench and eyewash is popular in workplace where fire and chemical spillages may occur. All control valves are the instant action, stay opened type of ball valve. This unit also comes with foot pedal.

ECB 10022 SS
Floor Mounted Combination Unit of Drench Shower and Eyewash with Stainless Steel Bowls c/w Foot Pedal

| |
|---|
| Eyewash Bowl: |
| 280mm (11") bowl in highly polished stainless steel. |
| Eyewash Sprayheads Assembly: |
| Chrome-plated brass with ABS sprayheads assembly with twin soft-flow eyewash heads and instant flip-open protective dust-cover. The built in automatic pressure compensating valve assures safe steady flow under varying water supply conditions. Sprayheads also includes a filter to protect users against particles from the water flow which may be damaging to the eyes and face. |
| Control Valve: |
| 1 1/4" fast-action stainless steel ball valve is used for the shower assembly with the stainless steel pull rod. 1/2" fast-action stainless steel ball valve is used for the eyewash assembly with the stainless steel push plate. |
| Pedestal: |
| 250mm (10") aluminium pedestal with 3 mounting holes for 9mm bolts. Pedestal is brightly epoxy powder coated in yellow. |
| Waste: |
| 1 1/4" IPS. |
| Signage: |
| Drench shower and Eyewash. |
| Options: |
| Please refer to ECB 10020 AB, ECB 10001, ECB 10000, ECB 10020 SS, ECB 10440. |
| Compliance: |
| ANSI Z358.1-2004 |
| Pipe Threads: |
| Pipe threads in accordance to BS 21 or DIN 259 are supplied as standards. NPT pipe threads are also available upon request. |